UNIVERSITY OF CALIFORNIA, SANTA BARBARA

BERKELEY • DAVIS • IRVINE • LOS ANGELES • MERCED • RIVERSIDE • SAN DIEGO • SAN FRANCISCO



SANTA BARBARA • SANTA CRUZ

OFFICE OF DESIGN & CONSTRUCTION SERVICES and PHYSICAL FACILITIES

CONTRACTING SERVICES Building 439 Santa Barbara, California 93106-1030 Telephone (805) 893-3356 Fax (805) 893-8592

SENT VIA:	
	\boxtimes

FAX ON THIS DATE HAND DELIVERY ON THIS DATE FEDERAL EXPRESS ON THIS DATE UNITED PARCEL SERVICE ON THIS DATE

HOLDERS OF PLANS AND SPECIFICATIONS:

Room 1508 Renovation De La Guerra Bldg. 549 Project No. FM100222S/987756 Addendum No. 2

February 8, 2011

Enclosed is **ADDENDUM NO. 2** to the Construction Documents on the above-captioned project.

Bid date is Tuesday, February 15, 2011 at 2:30 PM to be held at:

CONTRACTING SERVICES Facilities Management, Bldg. 439, Door #E, Reception Counter University of California, Santa Barbara Santa Barbara, CA 93106-1030.

Late arrivals shall be disqualified. Please allow time for unforeseen traffic delays, securing a parking permit and potential parking problems.

Anna Galanis Director, Contracting Services

ADDENDUM NUMBER 2

to the

CONSTRUCTION DOCUMENTS

February 8, 2011

GENERAL

The following changes, additions or deletions shall be made to the following document(s) as Indicated; all other conditions shall remain the same.

I. DRAWINGS

Item No.

1. <u>Sheet A4.1 Door & Window Details & Schedule:</u>

Revise Door Schedule as shown on attached Drawing A4.1, Delta 1 dated Feb. 4, 2011.

END OF ADDENDUM NO. 2

	DOOR SCHEDULE																		
	NO NO	а Ш	DOOR SIZE	SIZE						DETAIL				HDWR SET					
	\cup][U × H	THK	MAT	FIN	GLZ	MAT	₽IN	ΗE	AD	JA	MB	SILL	H H	및 H		REMARKS	
ТХШ	1	Д	3'-6" x 6'-10" ± 2'-2" x 6'-10"	³ ⁄4"	ALUM	CLR	TEMP	STL	PT	-			-		ØIR) NO		W EXTERIOR DOOR W/ OPERABLE SIDE PAN ATCH (E) DOOR 2. PAINT FRAME TO MATCH 1	
Ш	2	-	(E) 3' -6" × 6'-10"		ALUM	CLR	TEMP	STL	PT	-			-		Ø2	\sum	(E) ENTRY DOOR TO REMAIN. PAINT FRAME		
	3	-	(E) 4'-Ø" × 6'-8"		ωp	PT	-	WD	PT	-			-		Ø3)	(E) BI-FOLD DOORS TO REMAIN. PAINT PE		
₽ ₽	4	в	3'-Ø" × T'-Ø"			ST	TEMP	ALUM	CLR	32/A4.1		32/	A4.1		Ø4)	FR	ENCH DOOR W/ SAND BLASTED TEMPERED	
NTERIOR	5	в	3'-Ø" × T'-Ø"			ST	TEMP	ALUM	CLR						Ø4)			
ΪŻ	6	в	3'-Ø" × T'-Ø"			ST	TEMP	ALUM	CLR						Ø4				
	T	ß	3'-Ø" × 7'-Ø"	↓	$ \downarrow$	ST	TEMP	ALUM	CLR						Ø5)	\downarrow		\checkmark \checkmark	

DOOR & HARDWARE NOTES

1. CLEAR WIDTH OF THE DOORWAY 15 32" MINIMUM.

- 2. BOTTOM 10" OF DOOR HAS A SMOOTH, UNINTERRUPTED SURFACE THAT ALLOWS THE DOOR TO BE OPENED BY A WHEELCHAIR FOOTREST WITHOUT CREATING A TRAP OR HAZARDOUS CONDITION.
- 3. EFFORT TO OPERATE DOORS: INTERIOR DOORS 5 POUNDS MAXIMUM PRESSURE TO OPERATE. EXTERIOR DOORS 81/2 POUNDS MAXIMUM.
- 4. GENERAL PURPOSE EGRESS DOOR LOCKING / LATCHING HARDWARE SHALL COMPLY WITH THE CALIFORNIA REFERENCED STANDARDS CODE (CRSC), SECTION 12-10 202, AS ADOPTED BY THE STATE FIRE MARSHAL. LEVER HANDLES SHALL COMPLY WITH SUBSECTION (F): LEVERS MUST BE CURVED AND SHALL RETURN TO WITHIN $\frac{1}{2}$ INCH OF THE DOOR.
- 5. EXIT DOORS ARE OPERABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR ANY SPECIAL KNOWLEDGE OR EFFORT.
- 6. LATCHING AND LOCKING DOORS THAT ARE HAND OPERATED ARE OPERABLE WITH A SINGLE EFFORT. LEVER TYPE HARDWARE.
- 7. OPENING HARDWARE IS CENTERED AT 40' ABOVE FINISH FINISH FLOOR.
- 8. DOOR CLOSURES, IF PRESENT, MUST BE SET SO THAT IT TAKES AT LEAST 3 SECONDS TO CLOSE FROM AN OPEN POSITION OF 10 DEGREES TO WITHIN 3" OF THE LATCH.

DWG. 549-312

NEL TO FRAME AT DOOR 2. TO MATCH EXISTING. FINISH SCHEDULE. GLASS PANEL \checkmark 4 FEB 2011

C20590 J. Allen Zimmer AlA Gregory C Rech AlA 1530 Chapala Street Santa Barbara, CA ph 805 966–7141 fax 805 564–4121 Ó drawn by job number 10010 date 4 FEB 2011 sheet scale 3'=1'-Ø' revisions sheet index DOOR SCHEDULE OVATION SANTA BARBARA 549 BLDG NAO NAO чŬ GUERRA \mathbf{O} CALL CALL പ്പു $\overline{}$ **()** 4 ົວ \cap Ø₹ ШI